



MACHINING CONDITIONS

APGT 100304 PDER-ALU
LT 05

M0003089

Material Group	SAPPHIRE TOOLS	Material Example	Hardness	D.O.C		Feed		Vc		Advised D.O.C [mm]	Advised Feed [mm/t]	Advised Vc [m/min]	
				min[mm]	max[mm]	min[mm/t]	max [mm/t]	min [m/min]	max [m/min]				
NiTi Alloy	Ti Based	10	T40	-	0.3	5	0.08	0.15	30	50	2	0.12	35
			TiAl6V4	-	0.3	5	0.08	0.2	40	60	2	0.12	45
Aluminium	Al (<8%Si)	13	4% < Si < 8%	100 HB	0.3	9	0.1	0.18	250	600	3	0.14	400
			Si < 4%	60 HB	0.3	9	0.12	0.2	400	1200	3	0.14	500
Non-Metallic	Copper Alloys	14	CuZn30	100 HB	0.3	9	0.1	0.18	100	800	3	0.14	300
			Fiber Plastics	-	0.3	9	0.12	0.2	80	500	3	0.12	200
			Graphite	-	0.3	9	0.12	0.2	100	200	3	0.12	150
			Hard Rubber	-	0.3	9	0.12	0.2	80	300	3	0.12	150