



# MACHINING CONDITIONS

RD MT 10T3 M0 LT 3000

M0002225

| Material Group     | SAPPHIRE CUTTING TOOLS Group            | Material Example | Hardness                                | D.O.C    |          | Feed       |            | Vc          |             | Advised D.O.C | Advised Feed | Advised Vc |     |
|--------------------|---|------------------|---|----------|----------|------------|------------|-------------|-------------|---------------|--------------|------------|-----|
|                    |   |                  |   | min [mm] | max [mm] | min [mm/t] | max [mm/t] | min [m/min] | max [m/min] |               |              |            |     |
| Steel              | Non Alloyed                             | 1                | C35, Ck45, 1020, 1045, 1060, 28Mn6      | 125 HB   | 0.5      | 2.5        | 0.18       | 0.64        | 190         | 330           | 1            | 0.35       | 250 |
|                    |   |                  |   | 190 HB   | 0.5      | 2.5        | 0.18       | 0.64        | 190         | 300           | 1            | 0.35       | 220 |
|                    |   |                  |   | 250 HB   | 0.5      | 2.5        | 0.18       | 0.64        | 190         | 250           | 1            | 0.35       | 200 |
|                    | Low Alloyed                             | 2                | 42CrMo4, St50, Ck60, 4140, 4340, 100Cr6 | 230 HB   | 0.5      | 2.5        | 0.15       | 0.5         | 150         | 210           | 1            | 0.3        | 180 |
|                    |   |                  |   | 280 HB   | 0.5      | 2.5        | 0.15       | 0.44        | 130         | 190           | 1            | 0.27       | 150 |
|                    |   |                  |   | 180 HB   | 0.5      | 2.5        | 0.15       | 0.5         | 150         | 240           | 1            | 0.3        | 200 |
|                    |   |                  |   | 350 HB   | 0.5      | 2.5        | 0.15       | 0.44        | 130         | 170           | 1            | 0.27       | 140 |
|                    | High Alloyed                            | 3                | X40CrMoV5, H13, M42, D3, S6-5-2, 12Ni19 | 220 HB   | 0.5      | 1.8        | 0.12       | 0.44        | 90          | 150           | 0.8          | 0.27       | 130 |
|                    |   |                  |   | 280 HB   | 0.5      | 1.8        | 0.12       | 0.44        | 90          | 130           | 0.8          | 0.27       | 120 |
|                    |   |                  |   | 320 HB   | 0.5      | 1.8        | 0.12       | 0.36        | 60          | 110           | 0.8          | 0.24       | 100 |
|                    |   |                  |   | 350 HB   | 0.5      | 1.8        | 0.12       | 0.36        | 60          | 90            | 0.8          | 0.24       | 80  |
| Stainless Steel    | Austentic                               | 4                | 304, 316, X5CrNi18-9                    | 180 HB   | 0.5      | 2.5        | 0.15       | 0.5         | 190         | 250           | 1            | 0.3        | 220 |
|                    |   |                  |   | 240 HB   | 0.5      | 2.5        | 0.12       | 0.44        | 160         | 210           | 1            | 0.3        | 190 |
|                    | Duplex                                  | 5                | X2CrNiN23-4, S31500                     | 290 HB   | 0.5      | 2          | 0.12       | 0.36        | 70          | 130           | 0.8          | 0.24       | 100 |
|                    |   |                  |   | 310 HB   | 0.5      | 2          | 0.12       | 0.36        | 70          | 120           | 0.8          | 0.24       | 90  |
|                    | Ferritic & Martensitic                  | 6                | 410, X6Cr17, 17-4 PH, 430               | 200 HB   | 0.5      | 2.5        | 0.15       | 0.5         | 150         | 210           | 1            | 0.3        | 190 |
|                    |   |                  |   | 42 HRc   | 0.5      | 2          | 0.15       | 0.4         | 90          | 150           | 0.8          | 0.24       | 130 |
| Cast Iron          | Grey                                    | 7                | GG20, GG40, EN-GJL-250, N030B           | 150 HB   | 0.5      | 2.5        | 0.18       | 0.64        | 150         | 240           | 1            | 0.35       | 200 |
|                    |   |                  |   | 200 HB   | 0.5      | 2.5        | 0.18       | 0.64        | 150         | 220           | 1            | 0.35       | 180 |
|                    |   |                  |   | 250 HB   | 0.5      | 2.5        | 0.18       | 0.64        | 150         | 190           | 1            | 0.35       | 160 |
|                    | Malleable & Nodular                     | 8                | GGG40, GGG70, 50005                     | 150 HB   | 0.5      | 2.5        | 0.15       | 0.56        | 100         | 200           | 1            | 0.3        | 180 |
|                    |   |                  |   | 200 HB   | 0.5      | 2.5        | 0.15       | 0.56        | 100         | 180           | 1            | 0.3        | 150 |
|                    |   |                  |   | 250 HB   | 0.5      | 2.5        | 0.15       | 0.56        | 100         | 150           | 1            | 0.3        | 130 |
| NiTi Alloy         | Fe, Ni & Co Based                       | 9                | Incoloy 800                             | 240 HB   | 0.5      | 2          | 0.12       | 0.36        | 30          | 50            | 0.8          | 0.24       | 32  |
|                    |   |                  | Inconel 700                             | 250 HB   | 0.5      | 2          | 0.12       | 0.36        | 30          | 50            | 0.8          | 0.24       | 30  |
|                    |   |                  | Stellite 21                             | 350 HB   | 0.5      | 2          | 0.12       | 0.36        | 30          | 50            | 0.8          | 0.24       | 30  |
|                    | Ti Based                                | 10               | T40                                     | -        | 0.5      | 2          | 0.12       | 0.36        | 30          | 60            | 0.8          | 0.24       | 40  |
|                    |   |                  | TiAl6V4                                 | -        | 0.5      | 2          | 0.12       | 0.4         | 40          | 70            | 0.8          | 0.27       | 55  |
| Hardened Materials | Steel Chilled Cast Iron White Cast Iron | 11               | G-X300CrMo15                            | 55 HRc   | 0.3      | 0.6        | 0.1        | 0.28        | 30          | 60            | 0.3          | 0.18       | 40  |
|                    |   |                  | Ni-Hard 2                               | 400 HB   | 0.3      | 0.7        | 0.1        | 0.36        | 40          | 80            | 0.4          | 0.21       | 50  |
|                    |   |                  | X100CrMo13, 440C, G-X260NiCr42          | 45 HRc   | 0.3      | 0.9        | 0.1        | 0.36        | 40          | 80            | 0.5          | 0.21       | 60  |
|                    |   |                  |   | 50 HRc   | 0.3      | 0.7        | 0.1        | 0.32        | 40          | 70            | 0.4          | 0.2        | 55  |
|                    |   |                  |   | 55 HRc   | 0.3      | 0.6        | 0.1        | 0.28        | 40          | 60            | 0.3          | 0.18       | 50  |
| Aluminium          | Al (>8%Si)                              | 12               | AlSi12                                  | 130 HB   | 0.5      | 2.5        | 0.18       | 0.64        | 200         | 400           | 1            | 0.38       | 280 |